

HYGIENESPEICHER SSP HSK ECO HYGIENE

TECHNISCHE DATEN HSK RO

Typenbezeichnung	SSP 500 Puffer	SSP 800 Puffer	SSP 1000 Puffer	SSP 1500 Puffer
Inhalt (l)	480	720	890	1465
Max. Betriebstemperatur (°C)	95	95	95	95
Max. Betriebsdruck (bar)	3	3	3	3
Durchmesser o. Isolierung (mm)	650	790	790	1000
Gerätehöhe o. Isolierung (mm)	1.690	1.760	2.047	2.098
Kippmaß (mm)	1.720	1.791	2.076	2.151
Gewicht (kg)	110	140	145	275

		500	800	1000	1500
A	mm	1.310	1.340	2.047	2.098
B	mm	170	185	215	290
C	mm	70	72	103	150
D	mm Ø	550	650	650	900
E	mm	220	255	270	350
F	mm	1.200	1.200	1.480	1.390
G	mm	50	50	50	50
H	mm	110	125	155	225
1	"/mm	G 5/4" / 1.690	G 5/4" / 1.760	G 5/4" / 2.047	G 5/4" / 2.098
2	"/mm	G 5/4" / 1.420	G 5/4" / 1.455	G 5/4" / 1.750	G 5/4" / 1.740
3	"/mm	G 5/4" / 1.420	G 5/4" / 1.455	G 5/4" / 1.740	G 5/4" / 1.740
4	"/mm	G 1/2" / 1.340	G 1/2" / 1.380	G 1/2" / 1.650	G 1/2" / 1.660
5	"/mm	G 1/2" / 1.230	G 1/2" / 1.250	G 1/2" / 1.520	G 1/2" / 1.510
6	"/mm	G 5/4" / 1.150	G 5/4" / 1.130	G 5/4" / 1.400	G 5/4" / 1.410
7	"/mm	G 5/4" / 1.040	G 5/4" / 1.020	G 5/4" / 1.290	G 5/4" / 1.260
8	"/mm	G 5/4" / 900	G 5/4" / 940	G 5/4" / 1.175	G 5/4" / 1.160
9	"/mm	G 5/4" / 760	G 5/4" / 860	G 5/4" / 1.060	G 5/4" / 1.050
10	"/mm	G 1/2" / 660	G 1/2" / 765	G 1/2" / 765	G 1/2" / 940
11	"/mm	G 1/2" / 560	G 1/2" / 620	G 1/2" / 620	G 1/2" / 800
12	"/mm	G 5/4" / 470	G 5/4" / 500	G 5/4" / 500	G 5/4" / 660
13	"/mm	G 5/4" / 340	G 5/4" / 390	G 5/4" / 390	G 5/4" / 450
14	"/mm	G 5/4" / 220	G 5/4" / 255	G 5/4" / 270	G 5/4" / 350
15	"/mm	G 5/4" / 220	G 5/4" / 255	G 5/4" / 270	G 5/4" / 350
16	"/mm	G 5/4" / 110	G 5/4" / 125	G 5/4" / 155	G 5/4" / 225

