

## HYGIENESPEICHER SSP HSK ECO HYGIENE R1

### TECHNISCHE DATEN HSK R1

Typenbezeichnung	SSP 500 Puffer	SSP 800 Puffer	SSP 1000 Puffer	SSP 1500 Puffer
Inhalt (l)	480	720	890	1465
Max. Betriebstemperatur (°C)	95	95	95	95
Max. Betriebsdruck (bar)	3	3	3	3
Wärmetauscherfläche (m <sup>2</sup> )	1,6	2,0	2,8	3,6
Durchmesser o. Isolierung (mm)	650	790	790	1000
Gerätehöhe o. Isolierung (mm)	1.690	1.760	2.047	2.098
Kippmaß (mm)	1.720	1.791	2.076	2.151
Gewicht (kg)	136	180	205	310

		500	800	1000	1500
A	mm	1.310	1.340	2.047	2.098
B	mm	170	185	215	290
C	mm	70	72	103	150
D	mm Ø	550	650	650	900
E	mm	220	255	50	350
F	mm	1.200	1.200	1.480	1.390
G	mm	50	50	50	50
H	mm	110	125	155	225
I	mm Ø	490	630	630	G ¾" / 2.098
1	"/mm	G ¾" / 1.690	G ¾" / 1.760	G ¾" / 2.047	G ¾" / 1.740
2	"/mm	G ¾" / 1.420	G ¾" / 1.455	G ¾" / 1.750	G ¾" / 1.740
3	"/mm	G ¾" / 1.420	G ¾" / 1.455	G ¾" / 1.740	G ½" / 1.660
4	"/mm	G ½" / 1.340	G ½" / 1.380	G ½" / 1.650	G ½" / 1.510
5	"/mm	G ½" / 1.230	G ½" / 1.250	G ½" / 1.520	G ¾" / 1.410
6	"/mm	G ¾" / 1.150	G ¾" / 1.130	G ¾" / 1.400	G ¾" / 1.260
7	"/mm	G ¾" / 1.040	G ¾" / 1.020	G ¾" / 1.290	G ¾" / 1.160
8	"/mm	G ¾" / 900	G ¾" / 940	G ¾" / 1.175	G ¾" / 1.050
9	"/mm	G ¾" / 760	G ¾" / 860	G ¾" / 1.060	G ½" / 940

